




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>E21B 43/34, B01D 45/16</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/40834</b> (43) International Publication Date: <b>13 July 2000 (13.07.00)</b>
<p>(21) International Application Number: <b>PCT/EP99/10498</b></p> <p>(22) International Filing Date: <b>29 December 1999 (29.12.99)</b></p> <p>(30) Priority Data: <b>09/223,887</b>      <b>31 December 1998 (31.12.98)</b>      <b>US</b></p> <p>(71) Applicant (for all designated States except US): <b>SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel Van Bylandtlaan 30, NL-2596 HR The Hague (NL).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): <b>TJEENK WILLINK, Cornelis, Antonie [NL/NL]; Volmerlaan 8, NL-2288 GD Rijswijk (NL).</b></p>	<p>(81) Designated States: <b>AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</b></p> <p><b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: **METHOD FOR REMOVING CONDENSABLES FROM A NATURAL GAS STREAM, AT A WELLHEAD, DOWNSTREAM OF THE WELLHEAD CHOKE**



## (57) Abstract

The present invention relates to a method for removing condensables from a natural gas stream, at a wellhead, downstream of the wellhead choke thereof. In accordance with the invention there is provided a method for removing condensables from a natural gas stream at a wellhead, the method comprising the steps of: (A) inducing the natural gas stream to flow at supersonic velocity through a conduit of a supersonic inertia separator and thereby causing the fluid to cool to a temperature that is below a temperature/pressure at which the condensables will begin to condense, forming separate droplets and/or particles; (B) separating the droplets and/or particles from the gas; and (C) collecting the gas from which the condensables have been removed, wherein the supersonic inertia separator is part of the wellhead assembly downstream of the wellhead choke. There is also provided a device for removing said condensables from said natural gas that is part of the wellhead assembly downstream of the choke, a wellhead assembly comprising said device.